

# ENVIROGRAF® PRODUCT 5

## INTUMESCENT-COATED NON-FIBROUS SLABS



### DESCRIPTION

A high density fire-stop sponge with either white intumescent coating on both sides or black impregnated sponge that is easily cut with a sharp knife and can be painted over/decorated. An appropriate quantity of Envirograf® Jointing Compound is supplied.

### USE

Suitable for use as a permanent fire barrier, where no fibres are permitted (eg: including computer rooms, operating theatres, sterile areas, electronics areas, and food preparation areas. Where services pass through the slab, use Envirograf® Products 1, 7, 13, and 110.

### PERFORMANCE

Tested to BS476 Part 22 (1987), achieving integrity of 138 minutes. Also tested at VNE to European Standard EN1363-1 (2000).

### ORDERING REFERENCES :

| Ref                      | Dimensions (mm)  |
|--------------------------|------------------|
| <b>WHITE COATING</b>     |                  |
| NF50/ 500                | 50 x 500 x 1000  |
| NF50/ 750                | 50 x 750 x 1000  |
| NF50/1000                | 50 x 1000 x 1000 |
| <b>BLACK IMPREGNATED</b> |                  |
| BNF50/ 500               | 50 x 500 x 1000  |
| BNF50/ 750               | 50 x 750 x 1000  |
| BNF50/1000               | 50 x 1000 x 1000 |

PATENTED

