


ENVIROGRAF® PRODUCT 25

INTUMESCENT PROTECTION SLEEVE SYSTEM FOR CABLES

All Electrical Products to comply with the revised 17th Edition of the IEE Regulations and Document B of UK Building Regulations



DESCRIPTION

A complete unit giving fire and smoke protection to electrical and plumbing services passing through fire barrier walls made from block, brick, concrete, and hollow plasterboard. The system comprises three parts:

- (A) A semi-flexible tube 200mm or 600mm long that can be cut to the right size to suit the floor or wall. In case of fire, this will intumesce and fill the hole, preventing the spread of fire.
- (B) Two smoke protection units (one placed each side of the penetration) that allow the maintenance of services but, in a fire, prevent the spread of smoke. (See also Product 110).

USE

Fire barrier for use in walls and floors, where cables can be easily installed or removed.

PERFORMANCE

Tested to BS476 Part 22 (1987), achieving 130 minutes integrity in solid walls, and 67 minutes in hollow plasterboard walls. Also tested at VNE to European Standard EN1363-1 (2000).

ORDERING REFERENCES:



| Ref | Internal | External |
|------|----------|----------|
| ICP1 | 50mm | 65mm |
| ICP2 | 90mm | 115mm |
| ICP3 | 115mm | 150mm |
| ICP4 | 165mm | 210mm |

Add suffix /2 for 200mm long and /6 for 600mm long. Other sizes available.