

ENVIROGRAF® PRODUCT 138

ENVIROGRIP® FIRE-RESISTANT ADHESIVE

ENVIROGRIP™

FIRE RESISTANT DRY LINING ADHESIVE

**90 MINUTES FIRE PROTECTION
ACOUSTIC PROPERTIES
AND BETTER GRIP**

**HOLDS PLASTERBOARD TO ALL TYPES
OF BRICK, BLOCK, CONCRETE & TIMBER**

IDEAL FOR APPLYING CERAMIC TILES TO WALLS, BRICK, BLOCK, CONCRETE, PLASTERBOARD, CHIPBOARD AND WOOD-RELATED PRODUCTS. CAN BE USED IN SHOWERS AND DAMP AREAS.

MAINTAINS THE INTEGRITY OF THE BOARD AND THE SUBSTRATE IT IS APPLIED TO, BECAUSE NO NAIL OR SCREW HOLES ARE NEEDED.



1



APPLY AND LEAVE FOR 3 MINUTES

2

**PRESS BOARD TO WALL OR TIMBER
STUDDING. ENVIROGRIP® ALLOWS FOR
MOVEMENT OF BOARD ON CONTACT.
CAN BE PULLED OFF IF REQUIRED,
RE-POSITIONED AND RE-ADHERED.**

3

CAN BE PLASTERED AFTER 2 HOURS



INTUMESCENT SYSTEMS LTD
ENVIROGRAF HOUSE, BARFRESTONE,
DOVER, KENT, CT15 7JG
PHONE: 01304 842555 – FAX: 01304 842666
EMAIL: SALES@ENVIROGRAF.COM

