

ENVIROGRAF® PRODUCT 84

**FIREPROOF PAPER FOR UPGRADING LATH/PLASTER CEILING/WALLS
GIVING IN EXCESS OF ONE HOUR FIRE PROTECTION**



D E S C R I P T I O N

This is a 1000mm wide fire protection material (S/CEILING), applied in the same manner as wallpaper, but using Envirograf® adhesive type CA/N. Also available with bonded firecard 920mm wide (S/CP/CARD).

U S E

Apply to existing lath-and-plaster ceilings and walls, to upgrade them to 60 minutes of fire protection. The plaster must be well adhered to the laths, and any cracks can be filled with Envirograf® Product 61 (intumescent stopper). All previous distemper and paper must be removed before application of the Envirograf® fire protection material. If the surface is porous, it is advisable to apply Envirograf® Product 93 (stabilising and bonding liquid) in order to seal the surface. Decorative cornices can be painted with Envirograf® Product 105 (smooth-finish intumescent coating for lath-and-plaster and plasterboard). In the event of plaster being loose from the laths on a ceiling, Envirograf® Product 53 (under-floor fire barrier) can be utilised to provide fire protection.

P E R F O R M A N C E

This product has undergone several fire resistance tests employing the general procedures and criteria of BS476 Part 21 (1987), achieving 90 minutes of insulation and integrity.

O R D E R I N G R E F E R E N C E S :

S/CEILING Fireproof Material
S/CP/CARD Fireproof Material with bonded firecard
CA/N Ceramic Adhesive
See Product 93 (Stabond) for bonding and sealing fluid

PATENTED