

Hyload HouseBuilder



Product Data Sheet

High Performance DPC For Housing

December 2005

Features and benefits

- High performance DPC
- Suitable for domestic applications
- Superior performance to BS grade DPC products
- Hyload DPC Jointing Accessory range available with Hyload HouseBuilder DPC
- Standard and bespoke preformed cloak units available

Description

Hyload HouseBuilder has been developed to provide the house builder with a cost-effective alternative to traditional bitumen DPCs, at the same time offering vastly superior performance. It has been specially developed to provide long-term damp proofing for domestic applications and is suitable for use in housing up to three storeys high. When used as a cavity tray, Hyload HouseBuilder must be supported by the intel.

Hyload HouseBuilder is a polymeric DPC material ideal for damp proofing walls of brick, block, stonework or concrete in both solid or cavity wall constructions. Hyload HouseBuilder uses the same proven production technology as used with Ruberoid's Hyload Original DPC, which was the first system of its kind in the UK and was awarded the first ever Agrément Certificate in 1967.

Using Hyload HouseBuilder has significant advantages over traditional bitumen damp proof courses (BS 6398 DPCs) that have been used in housing for many years. Traditional DPCs can become stiff and brittle at low temperatures, making them liable to crack when unrolled on site. The strength and flexibility of Hyload HouseBuilder means that even in temperatures below freezing it will not suffer from cracking when folded or unrolled. Hyload HouseBuilder will remain supple and pliable and can be cut and trimmed without difficulty.

Hyload HouseBuilder has been awarded Agrément Certificate No. 97/3403.

Product details

Dimensions and weights	Hyload HouseBuilder
Nominal weight kg/m ²	1.1
Nominal thickness mm	0.9
Nominal length m	20
Roll widths mm	100, 112.5, 125, 150, 225, 300, 337.5, 375, 450

Product range

Hyload HouseBuilder DPC may be used with other Ruberoid damp proofing products for total waterproofing integrity.

These include:

- Preformed units. (standard and special)
- Ruberclose Insulated DPCs.
- Hyload DPC Jointing System
- Hyload DPC Lap Adhesive
- Hyload DPC Jointing Tape
- Hyload DPC Fixing Strip and Pins

Application

Hyload HouseBuilder DPC must be installed in accordance with Ruberoid's recommendations and the following British Standards:

BS 5628: Part 3, 2001 Code of practice for use of masonry. Materials and components, design and workmanship.

BS 8215: 1991 Code of practice for design and installation of damp proof courses in masonry construction.

BS 8000: Part 3: 2001 Workmanship on building sites. Code of practice for masonry.

The following installation procedures are essential:

Hyload HouseBuilder must extend through the full thicknesses of the wall or wall leaf, including pointing and rendering, and project beyond the external face by 5 mm.

The DPC must be sandwiched between an even bed of wet mortar, and perforations in adjacent courses of brickwork and must be completely filled with mortar.

All lap joints must have a 100 mm overlap and be completely sealed using Hyload DPC Jointing Tape or Hyload DPC Lap Adhesive.

Ruberoid preformed cloak units must be used at stop ends.

When using DPCs with boot lintels or similar construction, it is recommended that the material be installed following the lintel profile.

Other products

Full product literature, health & safety and technical sheets are available as downloads from our website www.ruberoid.co.uk or on request by email: marketing@ruberoid.co.uk

Ruberoid Building Products

Literature Enquiries

E-Mail: marketing@ruberoid.co.uk Website: www.ruberoid.co.uk

Customer Services

Appley Lane North, Appley Bridge, Wigan, Lancashire WN6 9AB
Tel: 0800 028 5573 Fax: 0800 013 5574 E-Mail: sales@ruberoid.co.uk

Technical & Design Services

Coney Green Road, Clay Cross, Chesterfield, S45 9HZ
Tel: 0844 412 7228 Fax: 0844 412 7229 E-Mail: technical@ruberoid.co.uk

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.