

PROTECTING MEMBRANES

Visqueen offer three different protection boards to suit a variety of applications. From a bitumen composition to a reinforced LDPE blend, the varying boards are all;

- Light and easy to handle: allows ease of storage and transferring on site.
- Easy to install – can be cut and shaped on site.

VISQUEEN PROTECTION BOARDS

Heavy Duty – a tough, durable and rot resistant bituminous board that protects DPMs and tanking DPMs against mechanical damage, pedestrian or vehicular traffic and puncture from backfilling. Available in 1m x 2m x 3mm board.

Light Duty – a strong corrugated plastic board that protects Stormwater, UDG, membranes from backfill. Also protects loose laid membranes from following trades. Available in 1.22mm x 2.44mm x 3mm board.

High Impact – a reinforced PE compound board that protects DPMs and tanking DPMs against mechanical damage, pedestrian or vehicular traffic and puncture from backfilling. Available in 1.22mm x 2.44mm x 1mm board.

Protect&Drain – acts as a heavy duty protection medium for Visqueen damp proofing, gas proofing and tanking membranes. The product is 6mm thick and supplied in rolls 1.1m x 50m.

INSTALLATION

Boards are loose laid and butt jointed. Where necessary the joints can be over taped with Visqueen Girth Jointing Tape applied equidistant over the junction. Ensure surfaces are clean and dry prior to application of tape. Apply pressure to the tape to ensure adhesion.

An example detail shows where protection boards are used.

EXTERNALLY TANKED LIFT PIT SUSPENDED FLOOR (SW-03)

